

# 1 Identification of the substance/preparation and of the company/undertaking

- · Product details
- · Trade name: n-butyl acetate
- Manufacturer/Supplier:

Choobineh Toos Chemical industrials Co.

No. 103, Chamran Ave, Chamran 5

Mashhad - IRAN

www.choobinehtoos.com

tel: +98 511 222 00 95 fax: +98 511 223 67 64

· Further information obtainable from: Product safety department.

## 2 Composition/information on ingredients

- · Chemical characterization:
- CAS No. Description 123-86-4 n-butyl acetate
- · Identification number(s)
- · EINECS Number: 204-658-1 · EU Number: 607-025-00-1

### 3 Hazards identification

- · Hazard description: Not applicable.
- · Information concerning particular hazards for human and environment:

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. R 10 Flammable.

R 66 Repeated exposure may cause skin dryness or cracking.

R 67 Vapours may cause drows ness and dizziness.

#### 4 First aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

## 5 Fire-fighting measures

- Suitable extinguishing agents:
  - CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- · Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.



· Trade name: n-butyl acetate

(Contd. of page 1)

### 7 Handling and storage

- · Handling:
- · Information for safe handling: No special requirement
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.

### 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

### 123-86-4 n-butyl acetate

PEL (USA) 710 mg/m<sup>3</sup>, 150 ppm

REL (USA)

Short-term value: 950 mg/m³, 200 ppm
Long-term value: 710 mg/m³, 150 ppm
TLV (USA)

Short-term value: 950 mg/m³, 200 ppm
Long-term value: 713 mg/m³, 150 ppm

WEL (Great Britain) Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

- · **Additional information:** The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection: Not required.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection



Tightly sealed goggles



· Trade name: n-butyl acetate

(Contd. of page 2)

## 9 Physical and chemical properties

· General Information

Form: Fluid

Colour: Colourless Odour: Fruit-like Change in condition

Melting point/Melting range: -76 °C
Boiling point/Boiling range: 124-128 °C

· Flash point: 27°C

· Ignition temperature: 370°C

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures

are possible.
• Explosion limits:
Lower: 1.2 Vol %

**Upper:** 7.5 Vol %

· Vapour pressure at 20°C: 10.7 hPa

Density at 20°C: 0.88 g/cm³
 Solubility in / Miscibility with

water at 20°C: 5 g/l

• pH-value (5 g/l) at 20°C: 5

· Viscosity:

Dynamic at 20°C: 0.7 mPas

### 10 Stability and reactivity

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Acute toxicity:
- · LD/LC50 values relevant for classification:

 Oral
 LD50
 13100
 mg/kg (rat)

 Dermal
 LD50
 >5000
 mg/kg (rabbit)

 Inhalative
 LC50/4 h
 21.0
 mg/l (rat)

· Primary irritant effect:

on the skin: No irritant effect.on the eye: Irritating effect.

· **Sensitization:** No sensitizing effects known.



· Trade name: n-butyl acetate

(Contd. of page 3)

# 12 Ecological information

· General notes:

Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

## 13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · **Recommendation:** Disposal must be made according to official regulations.

## **14 Transport information**

· Land transport ADR/RID (cross-border)



· ADR/RID class: 3 Flammable liquids.

· Danger code (Kemler): 30

· UN-Number: 1123 · Packaging group: III · Hazard label: 3

· Description of goods: 1123 BUTYL ACETATE

· Maritime transport IMDG:



· IMDG Class: 3 · UN Number: 1123

· Label 3

Packaging group: IIIEMS Number: F-E,S-D

• Proper shipping name: BUTYL ACETATE • Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 3 · UN/ID Number: 1123

· Label 3



· Trade name: n-butyl acetate

(Contd. of page 4)

· Packaging group: III

· Proper shipping name: BUTYL ACETATE

## 15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

- · Risk phrases:
  - 10 Flammable.
  - 66 Repeated exposure may cause skin dryness or cracking.
  - 67 Vapours may cause drowsiness and dizziness.
- Safety phrases:
- 2 Keep out of the reach of children.
- 25 Avoid contact with eyes.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing MSDS:** Product safety department.
- · Contact: Terminal Manager